

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED**

degussa.

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	1 / 12

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product information**

Trade name : 824-1013 COLORTREND® VENETIAN RED
Use of the Substance / : Non-aqueous colorant
Preparation
Company : Degussa Corporation
379 Interpace Parkway
Parsippany, NJ 07054
USA

Telephone : 973-541-8000

Telefax : 973-541-8040

US: CHEMTREC EMERGENCY : 800-424-9300
NUMBER

CANADA: CANUTEC : 613-996-6666
EMERGENCY NUMBER

Product Regulatory Services : 973-541-8060

2. HAZARDS IDENTIFICATION***** EMERGENCY OVERVIEW *****

Form-paste **Color-red** **Odor-Petroleum distillate odor.**

May cause eye, skin and respiratory tract irritation.
Combustible liquid and vapor.

POTENTIAL HEALTH EFFECTS**Eye contact**

According to test results on similar colorant base mixtures, this product is classified as a moderate eye irritant. May cause tearing, reddening and/or swelling.

Skin Contact

Moderate irritant according to test results on similar base mixtures.
Prolonged or repeated contact may result in defatting and drying of the skin causing skin irritation and dermatitis (rash).

Inhalation

Possibly irritating.
Excessive inhalation of solvent vapors may cause nasal and respiratory irritation and central nervous system effects including dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even death.

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED****degussa.**

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	2 / 12

Ingestion

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Chronic Health Hazard

Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On X-rays it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis producing materials such as silica. Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapours, mists or fumes should be minimized.

Short term exposures to talc may cause lung irritation. Long term excessive exposure to talc dust may cause talcosis, a pulmonary fibrosis which in turn may lead to severe and permanent damage to the lungs. NTP Toxicology and Carcinogenesis Studies of Talc revealed that there is some evidence of carcinogenic activity in male rats and clear evidence of carcinogenic activity in female rats. There was no evidence of carcinogenic activity in male or female mice.

Amorphous silica may cause respiratory irritation but does not cause silicosis based on animal testing by NIOSH.

Inhalation of high dust levels of barium sulfate may cause baritosis, an irritation of the lung tissue which is not incapacitating and usually is reversible.

Because this product is a free-flowing liquid or paste, dust inhalation is not an expected route of exposure.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Information on ingredients / Hazardous components**

Iron Oxide				
CAS-No.	1309-37-1	Percent (Wt./ Wt.)		30 - 60 %
Stoddard solvent; Low boiling point naphtha - unspecified				
CAS-No.	8052-41-3	Percent (Wt./ Wt.)		10 - 30 %
Talc, Magnesium silicate hydrate				
CAS-No.	14807-96-6	Percent (Wt./ Wt.)		10 - 30 %
Amorphous silica				
CAS-No.	7631-86-9	Percent (Wt./ Wt.)		1 - 5 %
Barium sulfate				
CAS-No.	7727-43-7	Percent (Wt./ Wt.)		1 - 5 %
Distillates (petroleum), hydrotreated light; Kerosine - unspecified				
CAS-No.	64742-47-8	Percent (Wt./ Wt.)		1 - 5 %

Other information

This material is classified as hazardous under OSHA regulations.

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED****degussa.***creating essentials*

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	3 / 12

4. FIRST AID MEASURES**Inhalation**

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If unconscious, evaluate the need for artificial respiration. Get immediate medical attention.

Skin contact

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Thoroughly wash clothing, shoes and protective equipment before reuse or discard. Get medical attention if irritation develops or persists.

Eye contact

Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Aspiration of material into the lungs may cause chemical pneumonitis (damage to lungs) which may be fatal.

5. FIRE-FIGHTING MEASURES

Flash point	38.33 °C , 101 °F
	Method: Pensky-Martens C.C.

OSHA Flammability Classification	Combustible Liquid
----------------------------------	--------------------

Suitable extinguishing media

Use water spray or fog, foam, dry chemical or CO₂.

Specific hazards during fire fighting

Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Further information

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED****degussa.**

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	4 / 12

6. ACCIDENTAL RELEASE MEASURES**Additional advice**

Absorb spill with inert material, then place in a chemical waste container. After removal, flush contaminated area with water and collect for disposal. Clean up spills immediately. Remove sources of ignition and ventilate area. Use a respirator and other protective equipment as outlined in Section 8. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

7. HANDLING AND STORAGE**Handling****Safe handling advice**

Keep away from heat. Keep away from sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed for all product transfers. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.

Storage**Requirements for storage areas and containers**

Keep in a dry, cool place.

Keep container closed when not in use.

Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component occupational exposure guidelines****• Stoddard solvent; Low boiling point naphtha - unspecified**

CAS-No. 8052-41-3

Control parameters 100 ppm
500 ppm
2900 mg/m³
100 ppm
525 mg/m³

Time Weighted Average (TWA):(ACGIH)
PEL:(OSHA Z1)

Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

• Talc, Magnesium silicate hydrate

CAS-No. 14807-96-6

2 mg/m³
Respirable fraction.

Time Weighted Average (TWA):(ACGIH)

The value is for particulate matter containing no asbestos and <1% crystalline silica.

2 mg/m³

Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

MATERIAL SAFETY DATA SHEET
824-1013 COLORTREND® VENETIAN RED

degussa.

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	5 / 12

Respirable dust.

20millions of particles per cubic foot of air Time Weighted Average (TWA):(Z3)

2.4millions of particles per cubic foot of air Time Weighted Average (TWA):(Z3)

Respirable.

The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.

0.1 mg/m3 Time Weighted Average (TWA):(Z3)

Respirable.

The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.

0.3 mg/m3 Time Weighted Average (TWA):(Z3)

Total dust.

The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.

• **Amorphous silica**

CAS-No. 7631-86-9

20millions of particles per cubic foot of air Time Weighted Average (TWA):(Z3)

0.8 mg/m3 Time Weighted Average (TWA):(Z3)

The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.

10 mg/m3 Time Weighted Average (TWA):(ACGIH)
Inhalable particles.

3 mg/m3 Time Weighted Average (TWA):(ACGIH)
Respirable particles.

5 mg/m3 PEL:(OSHA Z1)
Respirable fraction.

15 mg/m3 PEL:(OSHA Z1)
Total dust.

5 mg/m3 Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA OEL)

Respirable fraction.

10 mg/m3 Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA OEL)

Total dust.

• **Barium sulfate**

CAS-No. 7727-43-7

MATERIAL SAFETY DATA SHEET
824-1013 COLORTREND® VENETIAN RED

degussa.

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	6 / 12

10 mg/m³
5 mg/m³
Respirable fraction. Time Weighted Average (TWA):(ACGIH)
PEL:(OSHA Z1)

15 mg/m³
Total dust. PEL:(OSHA Z1)

5 mg/m³
Respirable fraction. Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

10 mg/m³
Total dust. Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

• **Iron Oxide**

CAS-No. 1309-37-1
10 mg/m³
Fume. PEL:(OSHA Z1)

5 mg/m³
Fume. Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

5 mg/m³
Respirable fraction. Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

10 mg/m³
Total dust. Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

5 mg/m³
Respirable fraction. Time Weighted Average (TWA):(ACGIH)

Other information

The OSHA TWA and ACGIH TWA exposure values for talc are for asbestos free talc expressed as millions of particles per cubic foot (mppcf).

The exposure limit for iron oxide is for dust and fume as Fe.

The ACGIH TLV-TWA for amorphous silica is for the respirable fraction.

Engineering measures

Use explosion-proof ventilation equipment.

MATERIAL SAFETY DATA SHEET
824-1013 COLORTREND® VENETIAN RED

degussa.

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	7 / 12

Personal protective equipment

Respiratory protection

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hand protection

Use impermeable gloves.

Eye protection

Chemical resistant goggles must be worn.

Skin and body protection

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	paste
Color	red
Odor	Petroleum distillate odor.

Safety data

Boiling point/range	> 149 °C
Flash point	38.33 °C Method: Pensky-Martens C.C.
Relative density	1.7
Solubility/qualitative	Solubility in water: Slight.
Viscosity, dynamic	105 - 125 KU (25 °C)
Solvents and Volatiles Data	% VOC (gm/l) 296.28
Evaporation rate	Slower than butyl acetate

10. STABILITY AND REACTIVITY

Conditions to avoid	Avoid high temperatures and sources of ignition.
Materials to avoid	oxidizing substances Ethylene oxide and guanidinum perchlorate (incompatible with iron oxide.)

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED****degussa.**

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	8 / 12

11. TOXICOLOGICAL INFORMATION

Component Acute oral toxicity Iron Oxide
1309-37-1
LD50 Rat: > 5000 mg/kg

Stoddard solvent; Low boiling point naphtha - unspecified
8052-41-3
LD50 Rat: > 5000 mg/kg

Amorphous silica
7631-86-9
LD50 Rat: > 31600 mg/kg

Distillates (petroleum), hydrotreated light; Kerosine - unspecified
64742-47-8
LD50 Rat: > 15000 mg/kg

Component Acute inhalation toxicity Stoddard solvent; Low boiling point naphtha - unspecified
8052-41-3
LC50 Rat: > 5500 mg/m3 / 4 h

Distillates (petroleum), hydrotreated light; Kerosine - unspecified
64742-47-8
LC50 Rat: > 14100 mg/m3 / 4 h

Component Acute dermal toxicity Stoddard solvent; Low boiling point naphtha - unspecified
8052-41-3
LD50 Rabbit: > 3000 mg/kg

Amorphous silica
7631-86-9
LD50 Rabbit: > 2000 mg/kg

Distillates (petroleum), hydrotreated light; Kerosine - unspecified
64742-47-8
LD50 Rabbit: > 2000 mg/kg

Component Repeated dose toxicity Talc, Magnesium silicate hydrate
14807-96-6
Inhalation Rat(male)
Testing period: 791 d
LOAEL: 0.006 mg/l
target organ/effect: Lungs

Amorphous silica
7631-86-9
Long term or repeated exposure to amorphous silica has caused lung effects in animals.

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED**

degussa.

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	9 / 12

Component carcinogenicity
assessmentTalc, Magnesium silicate hydrate
14807-96-6

Short term exposures to talc may cause lung irritation. Long term excessive exposure to talc dust may cause talcosis, a pulmonary fibrosis which in turn may lead to severe and permanent damage to the lungs. NTP Toxicology and Carcinogenesis Studies of Talc revealed that there is some evidence of carcinogenic activity in male rats and clear evidence of carcinogenic activity in female rats. There was no evidence of carcinogenic activity in male or female mice.

Component General Toxicity
InformationBarium sulfate
7727-43-7

Inhalation of high dust levels of barium sulfate may cause baritosis, an irritation of the lung tissue which is not incapacitating and usually is reversible.

12. ECOLOGICAL INFORMATION

General Ecological Information No ecotoxicological studies are available.

13. DISPOSAL CONSIDERATIONS**WASTE DISPOSAL**

Advice on disposal

Waste must be disposed of in accordance with federal, state, provincial and local regulations. CONTAINER DISPOSAL: Empty containers by removing the top and inverting to allow all free-flowing product to drain. To meet regulatory criteria, the container is considered empty when less than 3% remains in the container. Additional special handling is not typically required and the empty container can be discarded with other non-hazardous trash. Note: Local disposal regulations may be more stringent and require additional restrictions or precautions. Customers should check with their local disposal company, municipal or state authority. Recycle of plastic or metal containers may require clean rather than empty containers. In this case the containers can be rinsed with mineral spirits until the containers are considered generally product free.

14. TRANSPORT INFORMATION**Sea transport IMDG-Code**

Class	3
UN-No	1263
Packaging group	III
EmS	F-E, S-E
Proper technical name (Proper shipping name)	

PAINT RELATED MATERIAL

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED****degussa.***creating essentials*

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	10 / 12

Air transport ICAO-TI/IATA-DGR

Class	3
UN-No	1263
Packaging group	III
Proper technical name (Proper shipping name)	
Paint related material	

Loading instructions/Remarks

IATA_C	ERG-Code 3L
IATA_P	ERG-Code 3L
CFR_INWTR	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.
CFR_RAIL	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.
CFR_ROAD	In the U.S. this material may be classified as combustible liquid. Combustible liquids are not regulated in packages 450 liters or less. This applies for shipments by road and rail only.

15. REGULATORY INFORMATION**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- None listed

CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- None listed

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard
- Fire Hazard

MATERIAL SAFETY DATA SHEET**824-1013 COLORTREND® VENETIAN RED**

degussa.

creating essentials

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	11 / 12

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- None listed

Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

State Regulations**California Proposition 65**

A warning under the California Drinking Water Act is required only if listed below:

- None listed

International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact Degussa Corporation Product Regulatory Department:

• Europe (EINECS/ELINCS)	Listed/registered
• USA (TSCA)	Listed/registered
• Canada (DSL)	Listed/registered
• Australia (AICS)	Listed/registered
• Japan (MITI)	Not listed/Not registered
• Korea (TCCL)	Not listed/Not registered
• Philippines (PICCS)	Not listed/Not registered
• China	Not listed/Not registered

16. OTHER INFORMATION**HMIS Ratings**

Health :	2*
Flammability :	2
Physical Hazard :	0

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

MATERIAL SAFETY DATA SHEET**degussa.****824-1013 COLORTREND® VENETIAN RED***creating essentials*

Material no.		Version	1.17 / US
Specification	139880	Revision date	08/05/2007
Order Number		Print Date	08/07/2007
		Page	12 / 12

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.