



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET

N1520

POLYPLEX OVERGLO CLEAR

DESCRIPTION: #N1520 POLYPLEX OVERGLO CLEAR is a transparent, non yellowing color blending medium for producing decorative effects on concrete, paper, or fabric for special faux finish . It is specially formulated with highest quality special water borne acrylic resin which provides excellent block resistance and gloss finish. It provides good penetrating color blending media on the porous surfaces and medium dense substrate. It dries to a flexible, weather resistant finish. It helps prevent color degradation by reducing the harmful effects of UV rays which cause premature fading.

RECOMMENDED USE:

#N1520 POLYPLEX OVERGLO CLEAR can be used for blending with colorants.

DIRECTIONS FOR TINTING

It can be tinted with **Mann Brothers colorants** to achieve best results.

Typical mixing ratios of colorant to #N1520 POLYPLEX OVERGLO CLEAR are 4 – 12 oz per gallon. Always test the desired effect before applying decorative techniques to finish final surface.

IMPORTANT !! BEFORE USING THIS PRODUCT, PERFORM A SPOT TEST to

- 1) test adhesion
- 2) determine if the clear causes any cracking or lifting of the surface coating and
- 3) determine that the clear gives the desired finish (It is especially important to test for clarity over dark colors).

APPLICATION: synthetic brush, a short nap roller (do not use foam roller) or spray.

Actual method of application varies upon the desired effect.

Caution! Do not apply in heavy coats. Do not allow wet film to puddle.

For best results apply 1 to 2 thin coats. Allow each coat to penetrate and dry thoroughly before applying another coat.

DRYING TIME: Dry to touch in 1 - 2 hours. To handle in 4 hours. Full cure in 3 days. .

It may be recoated in about 2 hour under normal atmosphere and application conditions.

Overnight dry is recommended before use. Drying time also depends on surface temperature and relative humidity.



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

THINNING: Thin with water if needed. Over-thinning may result in loss of hide.
For maximum durability and color retention use product as supplied.

COVERAGE: 300-400 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Flush material, hose and equipment with warm, soapy water.

V.O.C.: Less than 50 grams per liter.

ENVIRONMENTAL: Consult with regulatory and governmental agencies for allowable usage conditions and disposal methods.

CAUTION: Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: Do not apply if surface, container or air temperature is below **50 degree F**.

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use. Do not take internally. **Keep out of reach of children. Keep from freezing.**