

MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS

758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET

#380-01 COLOR THEMES SATIN 100% ACRYLIC

LONGER LASTING TRUE COLOR 100% ACRYLIC EXTERIOR/INTERIOR SATIN ENAMEL

DESCRIPTION COLOR THEMES SATIN 100% Acrylic is a versatile high-quality satin finish for all Exterior/Interior surfaces. Its tough, flexible film has excellent resistance to chalking, color-fading to UV ray, mildew and weathering. It has excellent hiding power, strong adhesion, scrubability, block resistance, and non-yellowing properties.

COLOR White and three tinted bases. Various ranges of custom colors are available upon request.

FINISH Satin. (20– 35% @60 gloss meter)

USES Exterior/Interior: Properly prepared and primed stucco, concrete, masonry, plaster, wood, metal surfaces.

SURFACE PREPARATION New works: All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil or other foreign materials that could cause adhesion problems. Allow new concrete, stucco, drywall or plaster to cure before application of primer and finish coats. Pre treat all galvanized or non-ferrous metal surfaces. Patch all voids, cracks, and holes with appropriate patching or caulking material. New surfaces should be sealed with suitable primer/sealer.

Old works: Power wash, scrape, sand and completely clean to remove any dirt, rust, chalk, grease, oil, wax, loose paint or any other foreign materials. Glossy surfaces should be dulled down for good adhesion.

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

PRIMER Drywall/Plaster: 86-00 – eco-Gard PVA SEALER
Stucco/Concrete: 71-01 – EVERBOND CONCRETE PRIMER

Wood: 73-01 - TOTAL PREP PRIMER

Metal: 74-00 - ALKYD METAL PRIMER
61-01 – FERRO CHEM PRIMER

MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS

758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

Physical Data:

Viscosity@77 F: 95-105 KU

Weight per gallon: 10.8 Lbs/Gal

Solid by Volume: 38.0 +2%

Solid by Weight: 50.0 +2%

Recommended film thickness per coat:

Wet: 3.8 mils Dry: 1.5 mils

APPLICATION	Brush, roll or spray. Maintaining a “wet edge” while brushing or rolling will reduce brush marks, lapping and side sheen discrepancies.
THINNING	Use at package consistency. If necessary, add water sparingly for good flow and workability.
COVERAGE	Approximately 300-350 sq. ft. per gallon. The actual coverage may vary depending on surface conditions and application technique.
DRYING TIME	Dry to touch in 2 hours. Recoat in 4 hours. The actual drying time may vary due to atmospheric conditions.
CLEAN-UP	Use soap and warm water.
VOC	Less than 50 grams/gal