



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET

5006-01 Hi-Hide Set White

DESCRIPTION: **Hi-Hide Set White** is a flat vinyl acrylic coating with excellent hiding and tinting properties, very good adhesion, hold out and toughness. It resists mud-cracking and touched up. Designed specifically for the professional set painter.

RECOMMENDED USES: It may be used on any interior wood, masonry, drywall or other properly prepared surface where a high hiding flat coat is desired. Use appropriate primers before applying the top coat.

SURFACE PREPARATION: Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins. All surfaces must be clean, dry, and free of dust, dirt, grease, rust, loose paint, or other foreign substances. Remove all loose, flaking, or chalking surfaces. On exterior, sandblast all loose, flaking or chalking surfaces. After sandblasting, apply a coat of conditioning primer before applying Set White.

APPLICATION: It may be applied with brush, roller or spray. One coat application: Apply a coat of Set White, reducing with water as required. Two Coat Application: 1st coat. Reduce each gallon of Set White with one quart of water. Finish Coat. Reduce as needed for good application. NOTE: Moisten brushes and rollers before using. Brushed and rollers which have been used in applying other material should be cleaned thoroughly before use. Provide fresh air ventilation during and after application.

DENSITY: 12.0 lb per gallon on white color, varies depending on colors

NON-VOLATILE(Wt %): 57.0 for white color

NON-VOLATILE(Vol%): 39.0 for white color

VISCOSITY: 100-105 KU

DRYING TIME: It may be recoated in about 1 hour under normal atmosphere and application conditions.

THINNING: Thin with water if needed. Over-thinning results the loss of hide.

COVERAGE: 250-400 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Warm, soapy water.

V.O.C.: 0 grams per liter.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: Do not apply if surface, container or air temperature is below **50 degree F**.

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use. Do not take internally. **Keep out of reach of children. Keep from freezing.**