

PRODUCT DATA SHEET

5111-0060 AQUA PARA LAC SEMI GLOSS

DESCRIPTION: Series 5111 AQUA PARA LAC are water base, hard, very clear, fast drying 100% acrylic lacquer finishes which provides a protective coating for interior walls and other interior surfaces. This product is available in high gloss, semi gloss, satin, flat, or sanding sealer.

RECOMMENDED USES: AQUA PARA LAC is used as a final sealer/topcoat over a variety of interior surfaces such as wood, masonite, canvas and plaster to protect painted finishes. It may also be as a water based glazing medium.

SURFACE PREPARATION: Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins. All surfaces must be clean, dry, and free of dust, dirt, grease, rust, loose paint, or other contaminants.

APPLICATION: spraying is recommended

DENSITY: 8.59 lb/gal
SOLID BY WEIGHT %: 29.7
SOLID BY VOLUME %: 26.9
V.O.C.: Less than 275 grams per liter.

DRYING TIME: It may be recoated in about 2 hour under normal atmosphere and application conditions. Overnight dry is recommended before use. Drying time also depends on surface temperature and relative humidity.

THINNING: Thin with water if needed. Over-thinning results the loss of hide.

COVERAGE: 250-350 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Warm, soapy water.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: Do not apply if surface, container or air temperature is below 50 degree F.

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use.

Do not take internally. Keep out of reach of children. Keep from freezing.