



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET # 5137 AQUA PARA LAC FOR BRASS

DESCRIPTION: Series 5137 AQUA PARA LAC FOR BRASS are water base, hard, very clear, fast drying 100% acrylic lacquer finishes which provides a protective coating for interior brass and nonferrous metal surfaces. This product is available in high gloss, semi gloss, flat.

RECOMMENDED USES: AQUA PARA LAC FOR BRASS is used as a final topcoat over a variety of interior surfaces such as brass and non ferrous metal, wood, masonite, canvas and plaster.

SURFACE PREPARATION: Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins. All surfaces must be clean, dry, and free of dust, dirt, grease, rust, loose paint, or other contaminants.

APPLICATION: spraying is recommended

DENSITY: 8.56 lb/gal for gloss

NON-VOLATILE(Wt %): 37 for gloss

NON-VOLATILE(Vol%): 39 for gloss

DRYING TIME: It may be recoated in about 2 hour under normal atmosphere and application conditions. Overnight dry is recommended before use. Drying time also depends on surface temperature and relative humidity.

THINNING: Thin with water if needed. Over-thinning results the loss of hide.

COVERAGE: 250-350 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Warm, soapy water.

V.O.C.: Less than 275 grams per liter.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of

spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: Do not apply if surface, container or air temperature is below **50 degree F**.

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use.

Do not take internally. **Keep out of reach of children. Keep from freezing.**