

# PRODUCT DATA SHEET

**#770-00**

## **VARA-FLOR ACRYLIC FLOOR ENAMEL**

**DESCRIPTION:** Series 770 VARA-FLOR acrylic floor enamel is a low luster acrylic floor enamel specifically designed for floors, but with many other uses. It has outstanding performance properties after 24 hours of dry time, including: excellent adhesion under damp conditions, outstanding wet abrasion resistance, minimum dirt pick-up, and resistance to soapy water, mild acids and alkalis.

**AVAILABLE COLORS:** White, Columbia gray, Navajo gray, Inca red, Aztec green, New brown, Raw umber, Burnt umber, Natural cream, Black, Neutral base.

**RECOMMENDED USES:** Series 770 VARA-FLOR acrylic floor enamel may be used on properly prepared interior and exterior concrete, or on primed or previously coated wood floors, steps, porches and railings, and metal or wood walkways. Because VARA-FLOR offers a hard, abrasion resistant, low-sheen surface, it is used by many people as a wall or trim paint wherever a durable, low sheen coating is desired.

**APPLICATION:** Applied with brush, roller or spray. Do not apply this paint when temperature is below 50 degrees Fahrenheit. In most cases of stock colors, one coat covers unless there is a drastic color change.

**SURFACE PREPARATION:** Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins.

**CONCRETE – Already – Painted:** Wire brush or sand all loose, chalking or flaking material from surface to be painted. Rinse well with water and allow to dry 2 to 3 hours before painting. (If surface is too wet, paint will not penetrate deep enough for good adhesion.) After surface has dried apply a coat of Series 770 VARA-FLOR acrylic floor enamel.

**CONCRETE – New or Unpainted:** If cement has a glossy surface only, use an etching solution to increase adhesion, then rinse with water; allow to dry thoroughly, and apply a coat of Series 770 VARA-FLOR acrylic floor enamel.

**WOOD and METAL – Already-Painted:** Wire brush or sand all loose, chalking or flaking material from surface to be painted. Remove all wax and polish: spot prime wood with Series 97 Plastic Primer; spot prime metal with Series 61 Ferro-Chem; then apply a coat of Series 770 VARA-FLOR acrylic floor enamel.

**WOOD and METAL – New or Unpainted:** Apply a coat of Series 97 Plastic Primer to wood surface; or a coat of Series 61 Ferro-Chem to metal surfaces, allow to thoroughly dry, then apply a coat of Series 770 VARA-FLOR acrylic floor enamel. Provide fresh air ventilation during and after application.

**DENSITY:** 10.3 lb per gallon on white color, varies depending on colors

**NON-VOLATILE(Wt %):** 50.6 for white color

**NON-VOLATILE(Vol%):** 38.8 for white color

**VISCOSITY:** 90 – 100 KU

**MANN BROTHERS** PREMIUM PAINTS & FINISHING PRODUCTS  
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

**DRYING TIME:** It may be recoated in about 2 hours under normal atmosphere and application conditions, overnight dry is recommended before use.

**THINNING:** Thin with water if needed; but if paint gets heavy, thin slightly with water only. Thin sparingly for spraying.

**COVERAGE:** 250 - 350 sq. ft. per gallon, depending on surface porosity and method of application.

**CLEAN UP:** Flush material, hose and equipment with warm, soapy water. Observe all applicable regulation

**V.O.C.:** Less than 50 grams per liter.

**ENVIRONMENTAL:** Consult with regulatory and governmental agencies for allowable usage conditions and disposal methods.

**CAUTION :** Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spraying mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

**WARNING:** Do not apply if surface, container or air temperature is below **50 degree F**.

**NOTICE:** Purchaser is responsible for legal disposal of containers. Close container after each use.  
Do not take internally. **Keep out of reach of children. Keep from freezing.**