



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET

#772-00

ACRY-LUSTRE SEMI GLOSS ENAMEL

DESCRIPTION: Series 772 Acry-Lustre semi gloss enamel is a water thinned, semi gloss vinyl acrylic enamel designed for a variety of surfaces. Series 772 has good film toughness, provides excellent adhesion and is free of paint odor. It is non toxic, non flammable, and fast drying. It will withstand many washings without losing its luster. Available in tinting bases for most residential and commercial applications.

Where to use it: Primed, sealed or previously painted surfaces.

SURFACE PREPARATION: Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMAN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Old Work: Sand or scrape all loose, flaking or peeling surfaces. Patch all cracks and holes. Spot prime all bare areas. On glossy surfaces, deaden gloss and create a slight tack.

New Work: Wood: Fill all nail heads, gouges, etc.; allow to dry and sand smooth. Prime wood with Total Prep Primer #73-00. Plaster: Fill all cracks, holes and gouges, then seal the surface with a coat of pigmented sealer.

APPLICATION: Applied with brush, roller or spray. Moisten brushes and rollers before using. Apply from full brush, using semi-circular strokes. Level or tip off by brushing lightly from dry or unpainted to painted areas. Avoid re brushing painted area. When rolling, apply from a full roller and avoid re-rolling back into painted areas. Do not apply this paint when temperature is below 50 degrees Fahrenheit.

DENSITY: 10.8 lb per gallon on white color, varies depending on colors

NON-VOLATILE(Wt %): 51.9 for white color

NON-VOLATILE(Vol%): 41.8 for white color

VISCOSITY: 90 – 105 KU

DRYING TIME: It may be recoated in about 4 hours under normal atmosphere and application conditions.

THINNING: It is packaged ready to use and thinning is not normally required. If thinning is required, however, thin only as a necessary up to one half pine clean water to each gallon of Series 772. Stir thoroughly before using.



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

COVERAGE: 300-350 sq. ft. per gallon, depending on surface porosity and method of application.

CLEAN UP: Flush material, hose and equipment with warm, soapy water. Observe all applicable regulation

V.O.C.: Less than 50 grams per liter.

ENVIRONMENTAL: Consult with regulatory and governmental agencies for allowable usage conditions and disposal methods.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spraying mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: Do not apply if surface, container or air temperature is below **50 degree F**.

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use.

Do not take internally. **Keep out of reach of children. Keep from freezing.**