

MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS

758N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET # 97-01 PLASTIC PRIMER

DESCRIPTION: Water Base Plastic Primer, series 97, is a fast drying water base multi-purpose primer. It is formulated with a 100% acrylic resin and has excellent adhesion over a variety of surfaces including plastic, wood, glass, ceramic tiles, etc.

RECOMMENDED USE: Interior and exterior.

SURFACE PREPARATION: Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins. All surfaces must be clean, dry, and free of dust, dirt, grease, rust, loose paint, or other foreign substances. Remove all loose, flaking, or chalking surfaces. **NOTE: When used on the wood, it may be raising of the grain. It is advisable to coat a small section of the wood to determine whether the primer can be used without any problems. If the stain is the problem, use a stain stopping primer.**

APPLICATION: Spray only. Spray as is. In a highly humid day, spray a small section to check drying characteristics and film integrity before finishing the entire job.

DENSITY: 11.16 lb per gallon on white color, varies depending on colors

NON-VOLATILE(Wt %): 48.9 for white color

NON-VOLATILE(Vol%): 32.9 for white color

VISCOSITY: 85 – 100 KU

DRYING TIME: It may be recoated in about 30-60 minutes under normal atmosphere and application conditions.

THINNING: None required. Reduce with a very slight amount of water if absolutely necessary.

COVERAGE: 250-350 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Warm, soapy water while the coating is still wet.

V.O.C.: Less than 100 grams per liter.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: Do not apply if surface, container or air temperature is below **50 degree F**.

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use. Do not take internally. **Keep out of reach of children. Keep from freezing.**

CONTAINS: GLYCOL ETHER EB, MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

FOR ADDITIONAL INFORMATION, SEE MATERIAL SAFETY DATA SHEET(MSDS) FOR THIS PRODUCT.