



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET

#5050-01 PVA STUDIO WHITE - Self priming flat

DESCRIPTION:

PVA STUDIO WHITE is interior Zero V.O.C. acrylic modified water based sealer and finish flat paint. This product is formulated with non hazardous material, Green Guard Biocide, no formaldehyde, no carcinogen. **PVA STUDIO WHITE** is economical and offers durable finish on drywall, plaster, masonry, and previously painted surfaces. It offers good hide and easy applications.

SURFACE PREPARATION:

All surfaces must be clean, dry, and free from dust, dirt, oil, mildew, rust, chalking, loose paint or all contaminants. Drywall surfaces must be free of sanding dust. In order to prepare surfaces properly, follow steps as described below.

- Clean surface with appropriate cleaner for removing the contaminant if any. Rinse thoroughly and let dry completely.
- Strip, scrape or remove all loose and peeling paint and sand to smooth edges.
- Lightly sand glossy areas. Vacuum sanding residues.
- Repair holes, cracks and other surface imperfections and seal with suitable primer before painting.

New plaster or masonry must be allowed to cure (30 days) before applying painting.

Poured or pre-cast concrete surface should be etched or abraded to increase adhesion after removing all form release agents and curing compounds. Remove any powders or loose particles before painting the primer.

Difficult substrates such as tannins stain bleeding from wood, new galvanized metal requires to be recommended by the coating consultant to get the right problem solving primer for your special needs.

Warning! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**
To protect yourself and your family, you may contact 1-800-424-LEAD or log on www.epa.gov/lead.

APPLICATION: Brush, roller or spray. Apply this paint when temperature is above 50 degrees Fahrenheit. Stir thoroughly before use.

DENSITY: 11.7 lb per gallon.

NON-VOLATILE (Wt %): 47.6

NON-VOLATILE (Vol %): 41.9

VISCOSITY: 105 KU to 115 KU

DRYING TIME: It may be recoated in about 30 minutes under normal atmosphere and application conditions. Drying time also depends on surface temperature and relative humidity.



MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

- THINNING:** Thin with water if needed. Over-thinning results the loss of hide.
- COVERAGE:** 250-400 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.
- CLEAN UP:** Warm, soapy water.
- V.O.C.:** Zero grams per liter.
- ENVIRONMENTAL:** Consult with regulatory and governmental agencies for allowable usage conditions and disposal methods. Do not pour leftover paint down the drain.
- SAFETY MEASURE:** Read the Material Safety Data Sheet. Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.
- CAUTION:** Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.
- WARNING:** Do not apply if surface, container or air temperature is below **50 degree F**.
- NOTICE:** Purchaser is responsible for legal disposal of containers. Close container after each use. Do not take internally. **Keep out of reach of children. Keep from freezing.**