

PRODUCT DATA SHEET

543-00 AquaVar Clear Satin and Sanding sealer

DESCRIPTION: #543 AquaVar Clear Satin and Sanding Sealer seals and finishes interior wood surfaces and many other substrates that require a clear coating. It gives a superior clear, tough film with optimal chemical resistance for cabinets, paneling, furniture, staircase railing and any interior surfaces such as wood, masonite, canvas and plaster to protect painted finishes.

#543 AquaVar Clear Satin and Sanding Sealer does faster dry for sanding than #544 AquaVar Clear Satin does.

This coating is not intended to use on floors.

Direction for use – Stir well before using, do not shake. This product is ready to brush or spray without reduction. Thinning is not usually necessary. If thinning is needed, use water.

Faux Finishing – AquaVar is an excellent decorative top coat over acrylic paint and wall paper. This product may also be as a water based glazing medium.

SURFACE PREPARATION: New Wood – Clean and sand with fine sandpaper(220 grit). Wipe out surface to remove all sanding dust. If a stain is needed, make sure all stain has penetrated into wood and excess stain is thoroughly wiped off the surface. Allow the stain to dry according to stain instructions before applying **AquaVar**.

Refinish – Clean and sand with fine sandpaper(220 grit). Wipe off surface to remove all sanding dust. Test AquaVar in small area. If the finish is not uniform flow, or is wrinkled, strip to bare wood and treat as new wood. **Do not apply over any lacquer sealers contain zinc stearate to avoid adhesion problems.**

APPLICATION: Test in an inconspicuous area to ensure desired results. Apply with a good clean nylon brush, short nap roller or spray.

DENSITY: 8.46 lb/gal

NON-VOLATILE(Vol %): 27.6

NON-VOLATILE(Wt %): 30.5

DRYING TIME: It may be recoated in about 1 hour under normal atmosphere and application conditions. Overnight dry is recommended before use. Drying time also depends on surface temperature and relative humidity.

THINNING: Thin with water if needed. Over-thinning results sagging and less film thickness.

MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS

758 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

COVERAGE: 250-350 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Warm, soapy water.

V.O.C.: Less than 250 grams per liter.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

WARNING: **Do not apply if surface, container or air temperature is below 50 degree F. Keep out of reach of children. Keep from freezing.**